

V2X Collaborative Perception

Jiahao Huang

Networked Intelligence for Comprehensive Efficiency (NICE) Lab

College of Information Science and Electronic Engineering

Zhejiang University

<http://nice.rongpeng.info/>



Sep. 18, 2025

Content



1 The Foundations of Collaborative Perception

- General Overview: Challenges and Motivation
- Universal Framework: From Raw Sensor to BEV Features

2 Mainstream Works

- Efficient Communication: Minimizing Communication Costs
- Air-Ground Collaboration: Overcome Occlusions
- Heterogeneous Collaboration: Addressing Model and Sensor Disparities
- New Paradigm: Beyond BEV Features

3 Conclusion

The Foundations of Collaborative Perception



General Overview

Why Collaborative Perception?

- Standalone perception has fundamental physical limits. V2X collaborative perception is the key to breaking these barriers and enabling next-level autonomous safety.
- Standalone Intelligence: Inherent Blind Spots & Hazards^a.
- Enabling Technologies: 5G & Semantic Communication^b.
- The V2X Vision: Achieving Collective Traffic Efficiency.

^aJ. Cui et al., "Coopernaut: End-to-end driving with cooperative perception for networked vehicles," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2022, pp. 17 252–17 262.

^bS. Chen et al., "Vehicle-to-everything (v2x) services supported by lte-based systems and 5g," *IEEE communications standards magazine*, vol. 1, no. 2, pp. 70–76, 2017 .




Figure: Coopernaut:
End-to-End Driving with
Cooperative Perception

Paradigm of Collaborative Perception: Fusion¹



How to fuse information?

- **Intermediate Fusion** is Widely adopted, best trade-off between high perception performance and low communication overhead.
- **Early Fusion:** Agents share **raw sensor data** (e.g., LiDAR point clouds, camera images), requiring high communication bandwidth.
- **Late Fusion:** Agents exchange only **final detection results** (e.g., bounding boxes), constrained by individual agent capabilities.
- **Intermediate Fusion:** Agents transmit **neural network-extracted features** (often BEV-formatted), balancing performance and bandwidth.




Figure: Fusion Methods

¹S. V. Balkus et al., "A survey of collaborative machine learning using 5g vehicular communications," *IEEE Communications Surveys & Tutorials*, vol. 24, no. 2, pp. 1280–1303, 2022 .

Paradigm of Collaborative Perception: Pipeline



Gold-Standard

■ Universal Pipeline: Extract → Share → Fuse

- Input $\xrightarrow{\text{Raw Sensor Data: Point Cloud from Lidar, Pixels from Camera}}$
- Individual Feature Extraction $\xrightarrow{\text{Individual Perception}}$
- Feature Compression and Broadcasting^{ab} $\xrightarrow{\text{Intermediate Feature}}$
- Information Aggregation $\xrightarrow{\text{Fused Intermediate Feature}}$
- Perception and Prediction Heads $\xrightarrow{\text{Bounding Box}}$ Output




Figure: Pipeline




Figure: Collaboration

^aT.-H. Wang et al., “V2vnnet: Vehicle-to-vehicle communication for joint perception and prediction,” in *European conference on computer vision*, Springer, 2020, pp. 605–621.

^bR. Xu et al., “V2x-vit: Vehicle-to-everything cooperative perception with vision transformer,” in *European conference on computer vision*, Springer, 2022, pp. 107–124.

Paradigm of Collaborative Perception: Pipeline



Gold-Standard

■ Universal Pipeline: Extract → Share → Fuse

- Input $\xrightarrow{\text{Raw Sensor Data: Point Cloud from Lidar, Pixels from Camera}}$
- Individual Feature Extraction $\xrightarrow{\text{Individual Perception}}$
- Feature Compression and Broadcasting^{ab} $\xrightarrow{\text{Intermediate Feature}}$
- Information Aggregation $\xrightarrow{\text{Fused Intermediate Feature}}$
- Perception and Prediction Heads $\xrightarrow{\text{Bounding Box}}$ Output

^aT.-H. Wang et al., "V2vnet: Vehicle-to-vehicle communication for joint perception and prediction," in *European conference on computer vision*, Springer, 2020, pp. 605–621.

^bR. Xu et al., "V2x-vit: Vehicle-to-everything cooperative perception with vision transformer," in *European conference on computer vision*, Springer, 2022, pp. 107–124.




Figure: Pipeline




Figure: Collaboration



Neural Networks for V2X Feature Extraction

Backbone: PointPillars

- A foundational backbone for its efficiency in generating BEV features.
- **PointPillars^a**: Utilizes vertical columns of points (pillars) to create a 2D pseudo-image, enabling efficient 2D CNN processing while retaining 3D spatial information.
- **CenterPoint^b**: Detects object centers as keypoints and then regresses other properties like size, orientation, and velocity from center-point features (Anchor-Free).




Figure: PointPillars




Figure: CenterPoint

^aA. H. Lang et al., "Pointpillars: Fast encoders for object detection from point clouds," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019, pp. 12 697–12 705.

^bT. Yin et al., "Center-based 3d object detection and tracking," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021, pp. 11 784–11 793.

Object Detection or Semantic Segmentation



Why do we use Object Detection?^a:

- Object Detection is preferred over Segmentation due to its superior **communication efficiency** and direct relevance to **downstream tasks** like tracking and prediction.
 - **Object Detection**: Localize and classify distinct object instances using **bounding boxes**.
 - **Segmentation**: Assign a class label to every pixel in an image.

^aJ. Mao et al., "3d object detection for autonomous driving: A comprehensive survey," *International Journal of Computer Vision*, vol. 131, no. 8, pp. 1909–1963, 2023 .




Figure: Object Detection




Figure: Segmentation



Measurement²

- Average Precision (AP) at a given IoU threshold is the gold-standard metric for evaluating both the accuracy (Precision) and completeness (Recall).
- Precision and Recall: Tilting Board
 - Precision = $TP / (TP + FP)$: Which one is right?
 - Recall = $TP / (TP + FN)$: How many right ones are found?
- AP: Measure correctness with both Precision and Recall
 - P-R curve: Varying the confidence threshold.
 - AP: Area under the P-R curve.
- AP over IoU: Classic Metric
 - IoU: Intersection over Union.
 - AP over IoU: From right or wrong to how right.




Figure: P-R Curve

²T.-H. Wang et al., "V2vnet: Vehicle-to-vehicle communication for joint perception and prediction," in *European conference on computer vision*, Springer, 2020, pp. 605–621.



Datasets: From V2V to V2Rsu and UAV2UAV

- Datasets are evolving from vehicle-to-infrastructure to air-to-ground, driving research towards more **complex, integrated scenarios**.
 - DAIR-V2X(CVPR 2022)^a: Real World, Road-infrastructure Collaboration. It provides unmatched realism and **data fidelity**, but annotated data is **extremely scarce**.
 - UAV3D(NIPS 2024)^b: Virtual World(AirSim), UAV Collaboration. It offers massive **scalability** with perfect **ground truth** and meets "**sim-to-real**" domain gap.




Figure: DAIR-V2X




Figure: UAV3D

^aH. Yu et al., "Dair-v2x: A large-scale dataset for vehicle-infrastructure cooperative 3d object detection," in *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 2022, pp. 21 361–21 370.

^bR. Sunderraman, J. S. Ji, et al., "Uav3d: A large-scale 3d perception benchmark for unmanned aerial vehicles," *Advances in Neural Information Processing Systems*, vol. 37, pp. 55 425–55 442, 2024 .

Mainstream Works

Mainstream Works



Main Challenges:

- Research focuses on three core challenges: 1. Communication constraints (bandwidth, latency), 2. Perception limits (occlusions), and 3. System imperfections (heterogeneity, errors).
 - Communication constraints: **Bandwidth**^{ab} and **Temporal Asynchrony**.
 - Perception limits: **Occlusions** and Data Sparsity^c.
 - System imperfections: Localization Error, **Heterogeneity**^{de} and Security.

^aY. Hu et al., “Where2comm: Communication-efficient collaborative perception via spatial confidence maps,” *Advances in neural information processing systems*, vol. 35, pp. 4874–4886, 2022 .

^bY. Li et al., “Beyond bev: Optimizing point-level tokens for collaborative perception,” *arXiv preprint arXiv:2508.19638*, 2025 .

^cJ. Hao et al., “Is intermediate fusion all you need for uav-based collaborative perception?” *arXiv preprint arXiv:2504.21774*, 2025 .

^dY. Lu et al., “An extensible framework for open heterogeneous collaborative perception,” *arXiv preprint arXiv:2401.13964*, 2024 .

^eX. Gao et al., “Stamp: Scalable task and model-agnostic collaborative perception,” *arXiv preprint arXiv:2501.18616*, 2025 .



Where2Comm³: Overview (NIPS 2022)

- TLDR: Where2Comm pioneers on-demand communication: it intelligently asks for and shares only the **most critical information**—data from blind spots—to **maximize bandwidth efficiency**.




Figure: Overview of Where2Comm

³Y. Hu et al., "Where2comm: Communication-efficient collaborative perception via spatial confidence maps," *Advances in neural information processing systems*, vol. 35, pp. 4874–4886, 2022.



Where2Comm: Solution (NIPS 2022)

- Former Solution⁴: learn to **wait** for valuable but delayed information.
- Solution: **Pragmatic Communication**
 - Quantify the reliability via **confidence threshold**.
 - Multi-round broadcast for **request map**.
 - Pack and send most important **spatial information**.




Figure: Architecture of Where2Comm

⁴Y.-C. Liu et al., “When2com: Multi-agent perception via communication graph grouping,” in *Proceedings of the IEEE/CVF Conference on computer vision and pattern recognition*, 2020, pp. 4106–4115.



LIF⁵: Overview (arXiv 2025.7)

- TLDR: LIF introduces a novel hybrid late-intermediate fusion for air-ground collaboration, transmitting lightweight boxes and converting them to virtual BEV features to overcome **extreme UAV bandwidth limits**.





Figure: Overview of LIF

⁵J. Hao et al., "Is intermediate fusion all you need for uav-based collaborative perception?" *arXiv preprint arXiv:2504.21774*, 2025 .



LIF: Solution (arXiv 2025.7)

- Former Solution⁶: Transmitting intermediate features is still too costly for UAV.
- Solution: Transmit **lightweight detection results** but solves information loss.
 - Box-based Virtual Feature: Virtualizes received bounding box into pseudo-map and **inject into ego's intermediate BEV map**.
 - **Uncertainty-driven** communication scheme: only transmit information when collaborator is highly confident.





STAMP⁷: Overview (arXiv 2025.1)

- TLDR: STAMP enables true **heterogeneous collaboration** by using **feature translator** modules, allowing agents with different sensors and models to effectively understand each other.




Figure: Overview of Heterogeneity

⁷X. Gao et al., "Stamp: Scalable task and model-agnostic collaborative perception," *arXiv preprint arXiv:2501.18616*, 2025 .



STAMP: Solution (arXiv 2025.1)

- Former Solution⁸: Requires significant retraining and adaptation.
- Solution: **Plug-and-play** collaboration with **slight communication overhead**.
 - Adaptor-reverter: Transform unique BEV features into a unified **protocol domain**.




Figure: Overview of STAMP

⁸Y. Lu et al., "An extensible framework for open heterogeneous collaborative perception," *arXiv preprint arXiv:2401.13964*, 2024 .



CoPLOT⁹: Overview (arXiv 2025.8)

- TLDR: CoPLOT challenges the dominant BEV-based paradigm by proposing **communication with point-level tokens**, aiming to preserve more 3D information and improve efficiency.




Figure: Overview of CoPLOT



CoPLOT: Solution (arXiv 2025.8)

- Former Solution¹⁰: Grid-based BEV features suffer from computational overhead.
- Solution: Treat original points as token.
 - **State Space Models(Mamba)** to process sequence of point-level tokens.
 - **Semantic-Aware Reordering**: Injects frequency-domain features into the SSM to better distinguish foreground objects from background clutter.




Figure: Alignment Module in CoPLOT

Conclusion

Conclusions



Foundations:

- Pipeline: Extract $\rightarrow$ Share $\rightarrow$ Fuse
- Platform: OpenCOOD, modular design, from dataloader, processor to fuser.
- Backbone: PointPillars, extract 2D features while retaining 3D spatial info.
- Datasets: Sim to real gap, complex scenarios.

Latest Advances:

- Where2Comm: Transmit only necessary region for communication efficiency.
- LIF: 2D $\rightarrow$ 3D projector to retain ground information, Uncertainty-driven Filter.
- STAMP: Light-weight aligner for heterogeneous **sensor, model and tasks**.
- CoPLOT: From BEV fusion to Point-level Token communication.

Thank you

Jiahao Huang

Networked Intelligence for Comprehensive Efficiency (NICE) Lab

College of Information Science and Electronic Engineering

Zhejiang University

<https://nice.rongpeng.info>

Appendix

Paradigm of Collaborative Perception: Implementation



Gold-Standard

■ OpenCOOD^a (ICRA 2022): Standard Simulation Platform.

- Input $\xrightarrow{\text{Sensor Data with Logs: Relative pos, Sensor Params, etc}}$
- BaseDataset (Dataloader) $\xrightarrow{\text{Sensor Data indexed with timestamp}}$
- Preprocessor $\xrightarrow{\text{Intermediate Feature(Tensor of Voxel)}}$
- Information Aggregation $\xrightarrow{\text{Fused Intermediate Feature}}$
- Perception and Prediction Heads $\xrightarrow{\text{Bounding Box}}$ Output

^aR. Xu et al., "Opv2v: An open benchmark dataset and fusion pipeline for perception with vehicle-to-vehicle communication," in *2022 International Conference on Robotics and Automation (ICRA)*, IEEE, 2022, pp. 2583–2589.




Figure: TorchLoader




Figure: OpenCOOD

Where2Comm: Details



- **Confidence & Request Map:** First, the vehicle generates a confidence map from its own sensor data to find uncertain areas, then creates a request map from these "blind spots" to ask for help.
- **Message Packing:** Next, a responding vehicle uses this request map as a mask on its own feature map, **packing only the specifically requested information into a compact message**.
- **Feature Fusion:** Finally, the original vehicle fuses the received features with its own using an attention mechanism to intelligently weigh the data, filling its blind spots for a more complete perception.

$$\mathbf{C}_i^{(k)} = \Phi_{\text{generator}}(\mathcal{F}_i^{(k)}) \in [0, 1]^{H \times W},$$

$$\mathbf{R}_i^{(k)} = 1 - \mathbf{C}_i^{(k)} \in \mathbb{R}^{H \times W},$$

Figure: Confidence and Request

$$\mathbf{M}_{i \rightarrow j}^{(k)} = \begin{cases} \Phi_{\text{select}}(\mathbf{C}_i^{(k)}) \in \{0, 1\}^{H \times W}, & k = 0; \\ \Phi_{\text{select}}(\mathbf{C}_i^{(k)} \odot \mathbf{R}_j^{(k-1)}) \in \{0, 1\}^{H \times W}, & k > 0; \end{cases}$$

$$\mathbf{A}_{i,j}^{(k)} = \begin{cases} 1, \\ \max_{h \in \{0, 1, \dots, H-1\}, w \in \{0, 1, \dots, W-1\}} (\mathbf{M}_{i \rightarrow j}^{(k)})_{h,w} \in \{0, 1\}, \end{cases}$$

Figure: Message Packing

$$\mathbf{W}_{j \rightarrow i}^{(k)} = \text{MHA}_W(\mathcal{F}_i^{(k)}, \mathcal{Z}_{j \rightarrow i}^{(k)}, \mathcal{Z}_{j \rightarrow i}^{(k)}) \odot \mathbf{C}_j^{(k)} \in \mathbb{R}^{H \times W},$$

$$\mathcal{F}_i^{(k+1)} = \text{FFN} \left(\sum_{j \in \mathcal{N}_i \cup \{i\}} \mathbf{W}_{j \rightarrow i}^{(k)} \odot \mathcal{Z}_{j \rightarrow i}^{(k)} \right) \in \mathbb{R}^{H \times W \times D},$$

Figure: Feature Fusion

- **2D-3D Projection:** First, 2D detection results are transformed from the image plane to the 3D coordinate system. Second, the framework employs an uncertainty-driven communication mechanism to share high-quality detection results.
- **Vision-guided Positional Embedding (VPE):**
Transform 2D detection results into the ego-agent's BEV and generate a learnable positional embedding map to mark the locations of these targets.
- **Box-based virtual augmented BEV feature (BoBEV):**
Encode the geometric attributes (size, heading) and confidence scores of the received 3D bounding boxes into an augmented feature map.

$$\begin{bmatrix} u \\ v \\ 1 \end{bmatrix} = \frac{1}{z_c} \begin{bmatrix} f_x & 0 & c_x \\ 0 & f_y & c_y \\ 0 & 0 & 1 \end{bmatrix} \cdot \begin{bmatrix} x_c \\ y_c \\ z_c \end{bmatrix}$$

$$P(r) = r \cdot \left(\frac{u - c_x}{f_x}, \frac{v - c_y}{f_y}, 1 \right)$$

$$P_w = \begin{bmatrix} R & T \\ 0 & 1 \end{bmatrix} \cdot P_c$$

$$P_w(r) = T + r \cdot R \cdot \left(\frac{u - c_x}{f_x}, \frac{v - c_y}{f_y}, 1 \right)$$

Figure: Transformation

$$VPE_{m,n} = \begin{cases} Q \in \mathbb{R}^C, & (m,n) \text{ in } P_{bev} \\ 0, & \text{else} \end{cases}$$

$$BoBEV_{m,n} = \begin{cases} b_{3d}^{whl\theta s}, & (m,n) \text{ in } P_{bev} \\ 0, & \text{else} \end{cases}$$

Figure: VPE and CoBEV

- **Core Idea: Local Adaptation and Reversion:** First, each agent is equipped with a **local adapter** that maps its unique B3V feature to a unified, **shared protocol feature**. After receiving broadcasted features, each agent uses its **local reverter** to map the incoming protocol features back into its **own feature domain**.
- **For Adapter:** The objective is to minimize the gap between its adapted feature to a ground-truth protocol feature.
- **For Reverter:** Similarly trained to map features from the protocol domain back to agents' local feature.

$$\text{Adaptation: } F_{iP} = \phi_i(F_i), \quad \forall i \in \{1, 2, \dots, N\}$$

$$\text{Reversion: } F_{ij} = \begin{cases} \psi_j(F_{iP}), & \text{if } i \neq j \\ F_i, & \text{if } i = j \end{cases} \quad \forall i, j \in \{1, 2, \dots, N\}$$

Figure: Overview

$$\phi_i = \arg \min_{\phi_i} L_{\phi_i}(F_{iP}^{1:K}, F_P^{1:K}) \quad \text{where} \quad F_{iP}^k = \phi_i(F_i^k)$$

$$\psi_i = \arg \min_{\psi_i} (L_{\psi_i}(F_{Pi}^{1:K}, F_i^{1:K}) + L_{\psi_i}(F_{ii}^{1:K}, F_i^{1:K}))$$

$$\text{where } F_{Pi}^k = \psi_i(F_P^k), F_{ii}^k = \psi_i(F_{iP}^k)$$

Figure: Objective

$$L_{\phi_i}^d = \mathcal{L}_P(D_P \circ U_P(F_{iP}^{1:K}), \text{GT}_P)$$

$$L_{\psi_i}^d = \mathcal{L}_i(D_i \circ U_i(F_{Pi}^{1:K}), \text{GT}_i) + \mathcal{L}_i(D_i \circ U_i(F_{ii}^{1:K}), \text{GT}_i)$$

Figure: Loss Function