

How Can We Use Large Language Models (LLMs): A Brief Tutorial

Networked Intelligence for Comprehensive Efficiency (NICE) Lab
College of Information Science and Electronic Engineering
Zhejiang University
<http://nice.rongpeng.info/>



Aug. 18, 2025

Content



1 Decoder-only Architecture

- Causal Transformer
- Training and Inference

2 Training Large Language Models

- General Overview
- Pre-training
- Supervised Fine-tune(SFT)
- Reinforcement Learning with Human Feedback (RLHF)

3 Weight-based Evolution

- Fine-tuning with an Added Linear Head
- Fine-tuning with Natural Language

4 Text-based Evolution

- Prompt Engineering and In-context Learning
- Workflows & Agentic
- Self-refinement with iterative feedback


5 Conclusion

Decoder-only Architecture




Introduction to Causal Transformer

Open AI GPT Series: Generative Pre-trained **Transformer**¹





- GPT Series are **Decoder-only** transformer (**causal transformer**) architecture
- Most LLMs adopt the decoder-only architecture.



¹A. Vaswani et al., "Attention is All you Need," in *Advances in Neural Information Processing Systems*, vol. 30, Curran Associates, Inc., 2017.



Components of Causal Transformer²







- Architecture: Decoder-only transformer
- Token embedding: Switch token and vector
- Position embedding: Add positional information to token embeddings

²Visualizing Transformer Language Models, <https://jalammargithub.io/illustrated-gpt2>



Masked Self-Attention

Scaled Dot-Product Attention





- $\text{softmax}(\frac{QK^T}{\sqrt{d}})V$: Compute attention scores between tokens in the input sequence
- Masked: Prevent information leakage from future tokens during training



Masked Self-Attention

Multi-Head Attention




- $W_i^Q \in \mathbb{R}^{d_{\text{model}} \times d_k}$, $W_i^K \in \mathbb{R}^{d_{\text{model}} \times d_k}$, $W_i^V \in \mathbb{R}^{d_{\text{model}} \times d_v}$; $W^O \in \mathbb{R}^{hd_v \times d_{\text{model}}}$
- $d_{\text{model}} = \text{embedding_size}$, $d_k = d_v = d_{\text{model}}/h$
- Multi-head attention allows the model to jointly attend to information from different representation subspaces at different positions.



Overview of Architecture

Multiple decoder blocks stacked




- The process is identical in each block
- Each block has its own weights in both self-attention and the NN sublayers



Model Output

Convert the output vector to token





Training and Inference

■ Training Dataset Example: English → French




Figure: Training phase




Figure: Inference phase


■ Parallel training and autoregressive inference

Training Large Language Models

Overview of LLM Training



GPT Series: Generative **Pre-trained** Transformer




- **Pre-training:** Inculcate knowledge. Training the model to predict the next word using a massive amount of web data. This step results in a base model.
- **SFT:** a supervised fine-tuning step that makes the model more useful in following instructions and answering questions. This step results in an instruction tuned model or a supervised fine-tuning / SFT model.
- **RLHF:** fine-tuning with human feedback is a promising direction for aligning language models with human intent.




Overview of LLM Training

GPT Series: Generative **Pre-trained** Transformer




■ Technical route for training LLMs





Pre-training of LLMs³

- Labeled data for learning these specific tasks is scarce
- Leverage linguistic information from unlabeled data
- The effective objective in text representation learning – Next token prediction



Dataset	Quantity (tokens)	Weight in training mix	Epochs elapsed when training for 300B tokens
Common Crawl (filtered)	410 billion	60%	0.44
WebText2	19 billion	22%	2.9
Books1	12 billion	8%	1.9
Books2	55 billion	8%	0.43
Wikipedia	3 billion	3%	3.4

- $h_0 = UW_e + W_p$, $h_l = \text{Decoder}(h_{l-1}) \forall i \in [1, n]$, $P(u) = \text{softmax}(h_n W_e^T)$
- $U = (u_{-k}, \dots, u_{-1})$ is context vector; W_e and W_p are token and position embedding matrices.
- $L_1(\mathcal{U}) = \sum_i \log P(u_i \mid u_{i-k}, \dots, u_{i-1}; \Theta)$

³A. Radford et al., “Improving language understanding by generative pre-training,” 2018 .



Pre-training of LLMs⁴⁵

The three settings we explore for in-context learning

Zero-shot

The model predicts the answer given only a natural language description of the task. No gradient updates are performed.



One-shot

In addition to the task description, the model sees a single example of the task. No gradient updates are performed.



Few-shot

In addition to the task description, the model sees a few examples of the task. No gradient updates are performed.



Traditional fine-tuning (not used for GPT-3)

Fine-tuning

The model is trained via repeated gradient updates using a large corpus of example tasks.



- A single task system $p(\text{output}|\text{input})$
- A general system $p(\text{output}|\text{input}, \text{task})$
- LLM will begin to learn to **infer and perform the tasks demonstrated in natural language sequences** in order to better predict them, regardless of their method of procurement
- LLM will be performing **unsupervised multitask learning**

⁴ A. Radford et al., “Language models are unsupervised multitask learners,” 2019.

⁵ T. B. Brown et al., *Language models are few-shot learners*, 2020. doi: 10.48550/arXiv.2005.14165 arXiv: 2005.14165 [cs].



Supervised Fine-tune⁶

- Making language models bigger does not inherently make them better at following a user's intent
- Needed an initial source of instruction-like prompts to bootstrap the process

Collect demonstration data,
and train a supervised policy.

A prompt is
sampled from our
prompt dataset.



A labeler
demonstrates the
desired output
behavior.



This data is used
to fine-tune GPT-3
with supervised
learning.




Prompts & Text Dataset




Train Language Model

Initial Language Model



Human Augmented
Text (Optional)




⁶L. Ouyang et al., *Training language models to follow instructions with human feedback*, 2022. doi: 10.48550/arXiv.2203.02155 arXiv: 2203.02155 [cs].



Reward Model Training

- RL enables the agent to adapt to the **environment** make optimal decisions, relying only on feedback and **rewards** from interactions
- Need a reward model can predict the human-preferred output





RL Fine-tune⁷

- Continued enhancement of the language model without labeled data
- Environment: the language model itself


Optimize a policy against the reward model using reinforcement learning.

A new prompt is sampled from the dataset.

The policy generates an output.

The reward model calculates a reward for the output.

The reward is used to update the policy using PPO.




⁷More details can be found in tutorial "Evolution and Application of Reinforcement Learning (RL) in Large Language Models (LLMs)"

Weight-based Evolution



Linear Head⁸

The most effective way to transfer these learned representations to the target task.




- For a labeled dataset $\mathcal{C} = \{(x^1, \dots | y), \dots\}$, adding a linear head W_y
- $L_1(\mathcal{U}) = \sum_i \log P(u_i | u_{i-k}, \dots, u_{i-1}; \Theta), P(y | x^1, \dots, x^m; \Theta) = \text{softmax}(h_l^m W_y)$
- $L_2(\mathcal{C}) = \sum_{(x,y)} \log P(y | x^1, \dots, x^m; \Theta), L_3(\mathcal{C}) = L_2(\mathcal{C}) + \lambda L_1(\mathcal{C})$

⁸A. Radford et al., “Improving language understanding by generative pre-training,” 2018.



Fine-tuning with an Added Linear Head

- NetLLM⁹: networking-related use cases - viewport prediction, adaptive bitrate streaming and cluster job scheduling.
- Empowering the LLM to effectively process multimodal data in networking and efficiently generate task-specific answers.




⁹D. Wu et al., "NetLLM: Adapting large language models for networking," in *Proceedings of the ACM SIGCOMM 2024 Conference*, Sydney NSW Australia: ACM, 2024, pp. 661–678, ISBN: 979-8-4007-0614-1. DOI: 10.1145/3651890.3672268



Natural language for specialized domains¹⁰

- NetGPT: Synergizing appropriate LLMs at the edge and the cloud based on their computing capacity. Balancing low latency, resource efficiency, and customized outputs.
- Enhancing prompts with location-specific and user-specific context, while cloud models deliver high-quality responses.




¹⁰Y. Chen et al., "NetGPT: An ai-native network architecture for provisioning beyond personalized generative services," *IEEE Network*, vol. 38, no. 6, pp. 404–413, 2024. doi: 10.1109/MNET.2024.3376419



Natural Language Actions

- LLM as a policy that is updated as the agent interacts with the environment
- Using an interactive textual environment; Natural language as actions¹¹



See also in papers^{12, 13}

¹¹T. Carta et al., "Grounding large language models in interactive environments with online reinforcement learning," in *Proceedings of the 40th International Conference on Machine Learning*, A. Krause et al., Eds., ser. *Proceedings of Machine Learning Research*, vol. 202, PMLR, 2023, pp. 3676–3713.

¹²C. Tan et al., *Tool-aided evolutionary LLM for generative policy toward efficient resource management in wireless federated learning*, 2025. arXiv: 2505.11570 [cs.LG]. [Online]. Available: <https://arxiv.org/abs/2505.11570>

¹³R. Tan et al., *LLM4MAC: An LLM-driven reinforcement learning framework for mac protocol emergence*, 2025. arXiv: 2503.08123 [cs.NI]. [Online]. Available: <https://arxiv.org/abs/2503.08123>


Text-based Evolution



Prompt Engineering

Prompt engineering: users design various inputs for LLMs to generate desired outputs.

No requirements for extra training, producing output instantly based on user inputs.



- **In-context learning (ICL)**¹⁴: Let the LLM recognize and perform new tasks by leveraging contextual information – demonstrations, instructions, etc.
- **Chain-of-thought (CoT) prompting**: Providing reasoning steps, such as “Let’s think step by step” Contributing to the generation of reasoning LLMs¹⁵


¹⁴Z. Shi et al., “Why larger language models do in-context learning differently?” In *Proceedings of the 41st International Conference on Machine Learning*, ser. ICML’24, Vienna, Austria: JMLR.org, 2024.

¹⁵DeepSeek-AI et al., *Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning*, 2025. arXiv: 2501.12948 [cs.CL]. [Online]. Available: <https://arxiv.org/abs/2501.12948>



Methods to Workflows & Agentic

Complex scenarios like mathematical reasoning and multi-hop question answering





- **Planning for complex task solving**¹⁶: the task planner, the plan executor, and the environment. Forming workflows to solve problems
- **Agentic system**: LLMs operating as autonomous agents that can make decisions, use external tools, and execute tasks to achieve a goal, rather than just generating text responses.

¹⁶S. Yao et al., "Tree of thoughts: Deliberate problem solving with large language models," in *Advances in Neural Information Processing Systems*, A. Oh et al., Eds., vol. 36, Curran Associates, Inc., 2023, pp. 11 809–11 822.



Text Gradients and Back Propagation

Improving their outputs through iterative feedback and refinement



- feedback is actionable, containing concrete steps to further improve the initial outputs. *TextGrad*¹⁷, *Optimizer*¹⁸
- Prediction = LLM(Prompt + Question)
- Evaluation = LLM(Evaluation Instruction + Prediction)

¹⁷M. Yuksekgonul et al., “Optimizing generative ai by backpropagating language model feedback,” *Nature*, vol. 639, no. 8055, pp. 609–616, Mar. 20, 2025, issn: 0028-0836, 1476-4687. doi: 10.1038/s41586-025-08661-4 Accessed: Aug. 7, 2025.

¹⁸C. Yang et al., “Large language models as optimizers,” in *The Twelfth International Conference on Learning Representations*, 2023.

Conclusion

Conclusion



I have talked about

- Causal Transformer
 - Self attention and the architecture of the causal transformer
 - The training and inference process
- Large Language Models
 - The training process of the LLM (GPT series)
 - From pre-training to supervised fine-tuning and finally RLHF
- Evolution of the LLM
 - Parameter-based training and applications, including adding linear heads, natural language fine-tuning, natural language reinforcement learning
 - Text-based evolution, including prompt engineering, agentic systems and self-feedback reinforcement of LLMs

Thank you

Networked Intelligence for Comprehensive Efficiency (NICE) Lab
College of Information Science and Electronic Engineering
Zhejiang University
<https://nice.rongpeng.info>